



Aastra 142d

Handset for Aastra systems

DECToverSIP, NeXspan, A5000 and OpenCom (100/Aastra 800/1000)

DECT handset

Aastra 142d is the perfect DECT phone for Aastra platforms, which allows the complete integration of SIP and DECT communication.

This feature rich handset is a powerful tool for business communications on the go. It has a variety of convenient features such as hands-free operation, vibra-call, back-lit graphic display and caller lists. Call filter, alarm function and the display of time and date complete the features.

A transferable memory card stores 100 phonebook entries and specific data of the handset.

Hands free operation and the option to connect a headset allows easy operation.



Features

- » Hands-free operation
- » Back-lit display (color: amber)
- » Back-lit keypad
- » Transferable memory card (stores 100 phonebook entries and specific data of the handset).
- » 2.5 mm headset jack
- » Vibra-call
- » SOS-key for immediate connection to an emergency number
- » Quick Call feature on keys 1 to 9
- » Info-key for Messages and Caller list
- » Info and loudspeaker-key flashing when activated
- » Microphone mute function
- » 60 ring tones (30 short / 30 long)
- » Display of field strength, 4 steps
- » Adjustable volume control (receiver, loudspeaker), 8 steps
- » Ambient noise filter for loud environments
- » Telephone lock / alarm clock (alarm)
- » Auto-answer (for headset use)
- » Key lock, manually and automatically (1 minute timer)
- » Ring tone off (temporary)
- » Silent charging
- » Call filter (blocking / release)
- » Date / time (local format can be selected) **
- » Supports: call waiting, call hold, brokering, conferencing, call transfer (blind / consultation) **
- » Supports call forward: always, busy, no answer **
- » 13 Languages (Czech, English, Danish, Dutch, Finnish, French, German, Italian, Norwegian, Portuguese, Slovenian, Spanish, Swedish)

** if supported from PABX

Technical Data

- » Graphic display: back-lit, 5 lines (96 x 60 pixels), adjustable contrast
- » Standby time: up to 140 h EMEA / 125 h US
- » Talk time: up to 15 h EMEA / 18 h US
- » Batteries: 3 AAA (NiMH)
- » Charge time: max. 6 hours with empty batteries
- » Weight: 138 g incl. batteries
- » Dimensions (L x W X H): 146 x 52 x 28 mm
- » International AC Adapter for EMEA, North America and Australia
- » FCC / IC approval

System Support

- » OpenCom 100 / Aastra 800
(registration as OP 27 or 142d, respectively dependent on the release)
- » OpenCom 1000
(registration as OP 27 or 142d, respectively dependent on the release)
- » A5000 R 5.1 (with dedicated OMM R1.5 or higher)
- » NeXspan R 4.2 (with dedicated OMM R1.5 or higher)
- » DECToverSIP

Delivery units / Accessories

	Part No.
» Set Aastra 142d, International with handset, 3 batteries, belt clip, memory card, user guide, desktop charger and AC-power adaptor	68743
» Aastra 142d, Handset	68742
» Cradle with international AC Adapter	68737
» Belt clip	4514345
» Data cable (USB)	4510871
» Leader pouch	69592
» Headset T 171 (Standard)	4514 042
» Headset TC 500 (Comfort)	4514 281
» Charger Rack with 8 Rack Charger for 142d	69666
» AC Adapter for Charger Rack, international	69574



Aastra Technologies Limited

155 Snow Blvd.
Concord, Ontario
Canada L4K 4N9

www.aastra.com

AASTRA