

# EM Series Emergency Door Release

## Range: EM Series



*All doors which are designated as free exit routes require an emergency door release. Please check with the local Fire Officer to ensure compliance.*

### Technical Specification

Dimensions, flush	85 x 85 x 25mm
Dimensions, surface	85 x 85 x 58mm
Switch Output	Double pole
Switching current	3 Amps @ 12VDC
I P Rating	Internal use only
Warranty	24 months
Compliance	CE, ROHS & WEEE

The EM series of emergency door releases provide emergency unlocking of doors which are secured by electrical locks.

Two models are available:

The **EM200GDB** is a traditional “break-glass” unit, whereby the safety glass breaks when pressed and needs to be replaced to reset the unit.

The **EM201GDM** is a “resettable” unit, whereby the safety glass is dislodged when pressed and can be reset back to its normal position by use of a reset key.

Both units are double pole as standard - this allows for the control of the lock and provides a signal for monitoring of the unit if required (activate a sounder, trigger to an access control device etc). The EM series are supplied complete with a back box for surface fitting, but by removing the back box they can be fitted flush onto a standard UK back box. Full instructions are included.

Replacement glass for the **EM200GDB** and spare keys for the **EM201GDM** are available on request.

### Product Codes

<b>EM200GDB</b>	Double-pole, break glass
<b>EM201GDM</b>	Double-pole, resettable
<b>SPAREGLASS</b>	Replacement glass for EM201GDB
<b>EM201GDM-KEY</b>	Spare key for EM201GDM



ProTalk



Ideal for use with any of the ProTalk Door Entry Systems



For more information visit [www.provu.co.uk/protalk](http://www.provu.co.uk/protalk)