## **C-Line Magnetic Locks Entry Level**



## Range: Electromagnetic Locks













Multi-tenant Residential



## **Technical Specification**

Voltage: 12 or 24Vdc

**Current:** 610mA @ 12Vdc

305mA @ 24Vdc

Changeover (COM/NO/NC) Monitoring:

Indication: Bi-colour LED (surface only)

**Dimensions:** C3M11 228 x 38 x 27mm

 $(I \times w \times d)$ C3S11 255 x 45 x 26mm

C3S12 504 x 45 x 26mm C5S12 540 x 65 x 40mm The C-Line range of electromagnetic locks have been designed to provide a high performance, cost-effective solution to the competitive end of the magnetic locking market.

The range includes mortice and surface magnets, single and double, and 300kg or 500kg holding force (see below tables for details).

All the magnetic locks supplied in this range are monitored as standard, with a bi-coloured LED (surface models only) for visual verification of lock status and changeover relay for use if remote monitoring is required - with the focus on cost and performance, this range is certainly within the "more for less" category. Each model is supplied with the magnet, armature plate, template, fitting instructions and fixing kit.

All the magnets within the C-Line range are full compatible with the brackets, housings and accessories manufactured by CDVI. A standard warranty of 12 months applies to the range.

## **Product Codes**

**C3M11** Mortice magnet, monitored, 300kg C3S11 Surface magnet, monitored, 300kg

C3S12 Surface double magnet, monitored, 300kg C5S12 Surface double magnet, monitored, 500kg

(for single 500kg monitored magnet, use ECS8000M)

