

# Fanvil i60 SIP Door Phone

### **Description**

The i60 is a compact SIP door phone with a speed dial button and an IP65 rating for indoor and outdoor use. It supports various door-opening methods such as password, Bluetooth, IC/ID card, and DTMF Code for streamlined access management and is equipped with a 2 mega-pixel camera for audio and video communication. Compatible with SIP and ONVIF, it integrates with security systems and is ideal for villas, apartments, and communities.

#### **Main Features**



1 speed dial button



Equipped with a 2 mega-pixel HDR high-definition camera, it provides clearer imaging



IP65 high protection rating with wide temperature rate from -40°C to 70°C, suitable for harsh outdoor environments




Rich interfaces for security device connectivity



Supports the standard ONVIF protocol, providing high flexibility and excellent compatibility





### **Specifications**

Panel Type	Multi-apartment, Community, Villa
Keyboard	1 Speed-dial Button
Body	ABS+PC
Colors	Panel: black, Housing: Gunmetal
Sensor	1/2.9-inch, CMOS
Camera	2 Mpx, Support infrared
Viewing Angle	140°(FOV) 100°(Horizontal) 57°(Vertical)
Output video	H.264 (Baseline, Main Profile)
Light Sensitivity	0.1Lux
Card Storage	1,0000
Power Consumption  Power Supply	PoE:1.63~6.93W
	Adapter: 1.51~6.16W  DC 12V / 1A
	PoE 802.3af Class 3
Working Temperature	-40°C~+70°C
Storage temperature	-40°C~+70°C
Size of the Panel (LWH)	50*130*30mm
IP / IK Level	IP65
Installation	Wall-mounted
	Rain cover

## **Functional Capabilities**

Supported Protocols	SIP 2.0 over UDP/TCP/TLS
Lock Opening	IC Card, By DTMF Code, Remote Door Opening, BLE
Interface	Wiegand Input/Output Short Circuit Input/Output
Supported Wiegand	26, 34 bit
Supported ONVIF Types	Profile S
Supported Standards	DTMF, IC Card, Indoor Switch, BLE Cards 13.56 MHz
Talking Mode	Full duplex (High-definition Audio)
Additionally	Built-in relay, Motion detection, Tamper Alarm, TF Card, Open API